

## アタッチメント製品 スペック表

型 式 Models 小割圧砕機	台車規格 Carrier Weight (ton)	重 量 Real Weight (Kg)	最大開口 Jaw Opening (mm)	横 幅 Width (mm)	高 さ Height (mm)	設定圧力 Setting pressure (MPa)	先端破断力 Tip breaking force (kN)
TP - 03 V	3 ~ 4	280	430	630	970	21	160
TP - 05 V	4 ~ 5	320	490	715	1,120	21	180
TP - 10 V	6 ~ 9	650	620	880	1,370	25	210
TP - 15 V	10 ~ 16	1,150	780	1,220	1,910	30	460
TP - 15 V Mg付	12 ~ 16	1,450	780	1,220	1,910	30	460
TP - 25 V	20 ~ 22	2,050	880	1,370	2,040	32	830
TP - 25 V Mg付	20 ~ 22	2,400	880	1,800	1,700	32	830
TP - 25 VE 電柱	20 ~ 22	2,000	1,000	1,670	2,660	32	470
TP - 25 N Mg付	20 ~ 22	2,200	900	1,780	1,660	32	810
TP - 35 V	30 ~ 38	3,000	1,100	1,650	2,430	32	940
TP - 45 V	39 ~ 48	4,000	1,280	1,870	2,680	32	1,150
プラ・木材切断機	Carrier Weight	Real Weight	Jaw Opening	Width	Height	Setting pressure	Tip breaking force
TPE - 12 V	6 ~ 9	700	510	830	1,700	28	250
TPE - 17 V	10 ~ 16	950	650	1,000	1,920	30	350
TPE - 27 V	20 ~ 22	1,900	770	1,230	2,230	30	500
大割圧砕機	Carrier Weight	Real Weight	Jaw Opening	Width	Height	Setting pressure	Tip breaking force
TC- 015 V	2 ~ 3	150	300	580	840	18	120
TC - 03 V	3 ~ 4	300	430	740	1,100	21	220
TC - 05 V	4 ~ 5	450	480	740	1,200	21	190
TC - 10 V	6 ~ 9	720	620	980	1,480	25	290
TC - 15 V	12 ~ 16	1,300	750	1,410	1,700	30	400
TC - 15 SPV	12 ~ 16	1,400	900	1,410	2,080	30	400
TC - 25 V	20 ~ 22	2,150	1,000	1,520	2,200	32	720
TC - 25 RV旋回	20 ~ 22	2,050	1,000	1,520	2,300	32	720
TC - 25 SPV	20 ~ 22	2,400	1,200	1,870	2,440	32	750
TC - 25 SPRV旋回	20 ~ 22	2,450	1,200	1,870	2,550	32	750
TC - 35 V	30 ~ 38	3,900	1,300	2,150	2,830	32	920
TC - 35 RV旋回	30 ~ 38	3,950	1,300	2,150	2,700	32	920
TC - 45 V	39 ~ 48	5,400	1,600	2,400	3,050	32	1,340
TC - 55 V	50 ~ 65	6,800	1,600	2,460	3,100	32	1,620
TC - 75 V	70 ~ 85	9,800	1,900	2,070	3,300	32	1,980
TC - 80 V	90 ~ 110	12,000	2,000	3,100	3,890	32	2,550
KIC - 160 旋回	12 ~ 16	1,700	950	1,420	2,320	30	670
KIC - 200 旋回	20 ~ 22	2,400	1,100	1,640	2,640	32	970
KIC - 300 旋回	30 ~ 40	4,200	1,400	2,040	2,980	32	1,200
KIC - 450 旋回	40 ~ 50	5,000	1,600	2,350	3,220	32	1,500
鉄骨切断機	Carrier Weight	Real Weight	Jaw Opening	Width	Height	Setting pressure	Tip breaking force
TSX - 10 V	6 ~ 9	650	350	840	1,400	25	400
TSX - 15 V	12 ~ 16	1,400	400	1,100	1,780	30	420
TSX - 25 V	20 ~ 22	2,400	600	1,370	2,230	32	940
TSX - 35 V	30 ~ 38	4,600	770	1,550	2,500	32	1,160
TSX - 45 V	40 ~ 48	5,800	960	2,100	2,700	32	1,510
RTX - 550	12 ~ 16	1,300	550	1,050	1,930	32	580
RTX - 725	20 ~ 22	2,300	725	1,470	2,400	32	720
TSO - 350 V	6 ~ 9	650	520	860	1,670	25	300
TSO - 400 V	10 ~ 16	1,250	720	1,120	2,020	30	530
TSO - 500 V	20 ~ 22	2,250	850	1,400	2,600	32	840